Loc Tite 150

Loc Tite 150 is a thin-rib architectural standing seam metal roof panel with a 1½" mechanically seamed leg, built for commercial metal roofing projects in the Houston area where a clean, narrow seam line matters. Field-seam it to 90° for standard applications or 180° for higher wind uplift requirements, on roof slopes as low as 1:12. Concealed clips, 12" to 20" panel widths, and 24 gauge steel or .032 aluminum with a 35-year Kynar PVDF finish. UL 90 rated with Florida HVHZ and Miami-Dade approvals for hurricane-zone work. Comparable to PAC-CLAD PAC-150; fabricated and installed by Vogler Sheet Metal.

PRODUCT DETAILS

Seam	1½" thin rib · 90° single lock or 180° double lock
Attachment	Mechanically seamed, concealed clip
Min. slope	1:12
Widths	12–20"
Materials	24 ga steel · .032 alum
Key ratings	UL 90 · Miami-Dade NOA · Florida HVHZ / FBC · ICC-ES
Best for	Architectural look with low-slope capability; 180° seam for higher wind uplift

KEY FEATURES & BENEFITS

- Narrow architectural seam appearance
- Double-lock option for higher wind-uplift requirements
- Concealed attachment
- Suitable for slopes as low as 1:12
- Available in 12- to 20-inch panel widths
- 35-year Kynar PVDF finish